

# OPEN TOP OFFSHORE CONTAINER



## Product Features :

- Certification: DNV 2.7-1 / ISO 10855
- Optional slings: DNV 2.7-1 certified
- Design temperature to -40°C
- Multiple internal tie-down points
- Built-in lifting pad eyes and ISO corner castings for easy transport
- Standard forklift pockets
- Tarpaulins complete with roof bars
- Internal lashing points for securing cargo, each lashing bar or ring capable to withstand a force of 1,000kg
- Ideal for overheight cargo
- Hot Dip Galvanized unit available



Item		10'x8'x8'6"	20'x8'x8'6"	20'x8'x8'6" (with Side Door)
External Dimension	Length (mm)	2,991	6,058	6,058
	Width(mm)	2,438	2,438	2,438
	Height(mm)	2,591	2,591	2,591
Internal Dimension	Length (mm)	2,818	5,848	5,887
	Width(mm)	2,318	2,300	2,273
	Height(mm)	2,124	2,225	2,123
Gross Weight (kg)		10,000	20,000	25,000
Tare Weight (kg)		2,250	4,000	4,600
Max Payload (kg)		7,750	16,000	20,400

\*Actual specifications may vary due to product enhancement. Please contact us for more details.

## About us:

BSL Oilfield Services is a leading offshore equipment service provider, specializing in the supply and management of high-quality offshore containers, baskets, CCUs, tanks, and equipment.

For more details, please send email to [sales@bsloffshore.com](mailto:sales@bsloffshore.com)